

# Technical Data Sheet

## Solidcore skirting **FN TURN-X040** (XK040)



### Solidcore skirting **FN TURN-X040** (XK040)

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>             | <b>FN TURN-X040</b> (XK040)                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Basic material</b>          | Medium Density Fibreboard (MDF) covered with Polypropylen, elastic sealing-edges from TPE                                                                                                                                                                                                                                                                                                                                                               |
| <b>Surface</b>                 | Polypropylen Coating                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Colors</b>                  | Different uni colors to choose from or digitally printed decors                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Function</b>                | Clean and fluent transition to wall and floor<br>Hiding all hardwood floor joints                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Material characteristic</b> | <p>Durable combination of MDF and PP makes the skirting board resistant for any impacts, moisture or cleaning products.</p> <p>Elastic sealing-edges from TPE (Thermoplastic Elastomere) closing gaps at wall and floor.</p> <p>Smooth surface supporting cleaning and caring.</p> <p>Ground-adjusting sealing-edges preventing the penetrating from moisture and protects from dirt.</p> <p>Free from Halogens, Chlorides, Plasticizer, Silicones.</p> |


# Technical Data Sheet

## Solidcore skirting **FN TURN-X040** (XK040)

### Solidcore skirting **FN TURN-X040** (XK040)

**Dimensions** 40mm x 13mm x 2400mm

**Technical Drawing**



**Package**

1 PU (Package Unit) FN TURN-X040 = 15 pcs x 2,4 mtrs.

Products are packed in sturdy cardboard, securely sealed with adhesive tape and labelled with paper badges that clearly indicate the product name and the packaging unit (PU).

**Protective foil**

The surfaces of the uni-colored solidcore skirtings are covered with a transparent, removable protective foil.

**Product labeling**

Each item is labeled with the product name, dimensions, color code, EAN code, and the distributor's address.

**Gross Weight**

0,833kg

**Logistic Data**

|                             | Package Unit (PU) | Pallet size |
|-----------------------------|-------------------|-------------|
| Quantity [pcs]              | 15                | 675         |
| Weight [kg]                 | 12,5              |             |
| Dimensions [cm] (h x w x l) | ... x ... x 240cm |             |

**Tariff code**

4411 14 95

**Storage**

Skirting boards should be stored flat on a straight surface, in a dry place, and protected from weather conditions. Before installation, ensure that the boards have been stored at the place where they will be installed for at least 48 hours. This allows the plastic and the MDF solidcore to acclimate to the ambient conditions (humidity, temperature) and prevents any problems with material stress or deformation after installation.

**Certificates**



# Technical Data Sheet

## Solidcore skirting **FN TURN-X040** (XK040)



### Solidcore skirting **FN TURN-X040** (XK040)

**Check Wall surface** Before starting the wall surface must be checked to ensure that is suitable for the chosen fastening method. For materials containing plasticizers, the adhesive must always be tested for compatibility.

**Regulations** For the installation of this product, the applicable national standards, guidelines, and regulations, as well as technical references and recognized industry practices, must be observed. In particular, the following standards apply:

- DIN 18365 „Assessment and preparation of substrates for floor covering and parquet work“
- DIN 18560 „Screeds in construction“
- DIN 18202 „Specification of tolerances for buildings and structural components“
- VOB/C „General technical contract conditions for construction work“

Before installing the skirting boards, the following technical parameters should be checked:

**Check Wall Surface** The surface must be free of contaminants such as oil, wax, paint, plaster, adhesive residue, or other substances that impair adhesion. Mechanical cleaning such as sanding or grinding is often necessary.

**Check Wall Resistance** Surface must prove mechanical strength.

**Check Wall Sustainability** Loose or unsolid layers must be removed.

**Check Cracks/Joints** Cracks must be frictional-locked permanently. Don't cover Expansion joints – they must be preserved.

**Check Expansion Strips** Must be present on all adjoining floor fragments

**Check Climate Conditions**

| Air Temperature | Floor Temperature | Relative Humidity |
|-----------------|-------------------|-------------------|
| 18-26 °C        | 15-22 °C          | 40-65 %           |

**Check Levelness** Based on our extensive experience with skirting board installation, we recommend a flatness tolerance of less than 2 mm per meter, which is stricter than the deviations specified in DIN 18202. This ensures optimal installation quality and long-term customer satisfaction.

**Check Moisture** Background need to be dry. The following guideline values according to DIN 18560-1 „Screeds in Building Construction“ should not be exceeded:

| Cement Screed (CT) |            | Anhydrit Screed (CA) |            |
|--------------------|------------|----------------------|------------|
| heated             | unheated   | heated               | unheated   |
| < 1,8 CM %         | < 2,0 CM % | < 0,3 CM %           | < 0,5 CM % |

# Technical Data Sheet

## Solidcore skirting **FN TURN-X040** (XK040)



### Solidcore skirting **FN TURN-X040** (XK040)

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Installation</b>           | For quick, clean, and durable installation of the skirting boards, we recommend using the hot melt adhesive system with the FN Neuhofer Glue Applicator. This system ensures secure adhesion and allows efficient processing without long drying times.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Neuhofer Notching Tool</b> | Inside/Outside Corners without any additional parts<br>Easy processing inside/outside corners with skirting boards works without any additional forming elements – only the FN Neuhofer Notching Tool is required. This specially developed tool enables the absolute precise inside/outside corners and end caps in a time-saving and efficient method. Especially the closed surface of the outside corner during the work-process protects the profile core from moisture penetration.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Cleaning &amp; Caring</b>  | For just slightly dirt you can wipe off easily with a cleaning cloth.<br>When its deeply polluted use a customary cleaner, following the manufacturer's dosage instructions.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Non-use</b>                | Don't use any cleaning products that contains abrasive, acidic, or bleaching components or abrasive sponges. Avoid cleaning with scouring household sponges, as they may cause scratches.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Disposal</b>               | Waste Categorie: 20 01 39 recyclable Plastics<br>15 01 01 Paper and Cardboard Package<br>Separate collection<br>Recyclable Plastics in Yellow Bag / Yellow Bin<br>Clean Paperbag or Cardboard Package in Blue Bin or Recycling Container                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Regulations</b>            | Compliance with the Waste Management Act (AWG 2002) Incineration/Disposal - only after permission from the waste disposal company and the responsible authority.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Order Instructions</b>     | It is recommended that, within a customer project to use packaging units from a single delivery to avoid color variations.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Guarantee and Warranty</b> | <p>The client is obligated, under penalty of the contractor's release from liability, to notify the contractor in writing and with sufficient documentation of all claims, including but not limited to claims for defects and claims for damages, insofar as they are not excluded by the following provisions, without undue delay and at the latest within 14 days, regardless of whether the client has accepted the goods subject to reservation of rights, and to give the contractor or a third party commissioned by him the opportunity to inspect the goods in question and to submit a written report.</p> <p>The supplier provides a 3-month warranty for the flawless workmanship and functionality of the goods. The warranty period begins on the date of acceptance or delivery. During this period, the supplier will rectify any defects attributable to poor materials, faulty workmanship, or defective design free of charge.</p> <p>The warranty and liability under the aforementioned conditions are void if the delivered goods are altered, processed, or improperly handled.</p> |

# Technical Data Sheet

## Solidcore skirting **FN TURN-X040** (XK040)



### Solidcore skirting **FN TURN-X040** (XK040)

The contractor is liable only within the scope of mandatory law. Liability for consequential damages is entirely excluded. Should the contractor be held liable by a third party, the client shall indemnify and hold the contractor harmless to the extent that the contractor is not liable under this provision.

In the event of transport damage, the client must request the assessment and documentation of the damage from the responsible carrier immediately upon delivery or acceptance (notation on the delivery note and shipping document). The deadline for reporting transport damage not externally visible to the carrier and, in the case of postal shipments, is four days after receipt of the shipment. Missing items must be reported to the carrier immediately and before acceptance.

#### **User Recommendation**

Our user instructions are based on practical experience and are provided to help the user to achieve best results and customer satisfaction, but are considered non-binding advice from which no claims can be derived.

#### **General Terms and Conditions**

The General Terms and Conditions published on the FN website shall apply



# Technical Data Sheet

Solidcore skirting **FN TURN-X040 (XK040)**



Solidcore skirting **FN TURN-X040 (XK040)**

## Colors

|    | Color description  | Similar to RAL |
|----|--------------------|----------------|
| 1  | white              | RAL 9003       |
| 2  | white              | RAL 9016       |
| 3  | white              | RAL 9010       |
| 4  | cashmere           | RAL 7044       |
| 5  | cappuccino         | RAL 7032       |
| 6  | white aluminium    | RAL 9006       |
| 7  | window grey        | RAL 7040       |
| 8  | anthracite         | RAL 7016       |
| 9  | black              | RAL 9004       |
| 10 | metallic platinum  | RAL 860-M      |
| 11 | metallic champagne | RAL 830-M      |
| 12 | Digital printing   |                |

